



SPARTAN Power
Solutions



Industrial Range Powered by Cummins Model SC353 Generator set



General Performance Data

Prime Power	320KVA/256KW
Stand by Power	353KVA/282KW
Frequency/Speed	50Hz/1500rpm
Rated Power Factor(cosφ)	0.8
Standard Voltage	240V/415V
Phases	3



Engine	Brand	Cummins
	Model	6LTAA9.5-G1
Control module	Deepsea 6120	
Rated Current	445A	
Capacity of Breaker	630A	
Starting Voltage	DC24V	

Fuel consumption

Rated output	Fuel consumption rate	
100%Standby	200g/KW.h	78L/h
100%Prime	199g/KW.h	70L/h
75%Prime	196g/KW.h	52L/h
50%Prime	197g/KW.h	35L/h
25%Prime	210g/KW.h	18L/h

Standards followed

ISO9001	ISO14001
ISO8528	ISO12100
ISO13849	EN12601
GB12786	GB/T2820
IEC60034	IEC60204
CE	RETIE



Dimensions and Weights

Type	Open	Silent
Length(mm)	2780	3850
Width(mm)	1120	1400
Height(mm)	1830	2100
Weight(kg)	2300	3250
Base fuel tank volume (L)	540	540

Engine specification

Basic parameter

Manufacturer	Cummins
Model	6LTAA9.5-G1
No. of cylinder	6
Type	4 cycle, Vertical In-line
Prime Power	290kw /389HP
Standby Power	320kw /429HP
Induction system	Turbocharged and Air to Air Aftercooled
Governor	Electronic speed
Bore x Stroke	116.5x148mm
Displacement	9.5L
Compression ratio	16.6:1
Oil Capacity(Total)	32.4L
Coolant Capacity(Engine only)	11.1L
Cranking Motor Voltage	DC24V

Fuel System

Type Injection system	North Oil P7100 inline pump
Min. Allowable flow of fuel to fuel pump	78 L/h

Lubrication system

Oil Pressure	
---Idle speed	69kPa
---Rated speed	N/A
Max. allowable oil temperature	121°C
Oil Pan capacity - Low/High	27 /19L
Total system capacity	32.4L

Air induction system

Maximum allowable intake air restriction	
---with clean filter element	3.7kPa
---with dirty filter element	6.2kPa
Intake Air alarm temperature	82°C

Exhaust system

Max. allowable back pressure	8kPa
Standard exhaust pipe diameter	100mm

Cooling system

Coolant capacity	
---Engine only	11.1L
---Total system	57.1 L
---With heat exchangere	46L
Standard thermostat(modulating) range	82-95 °C
Minimum cap pressure	103kPa
Max. allowable top tank temerature for stand by/prime power	104/100 °C

Electric system

Min. recommended battery capacity (24V)	
---10°C(50°F) & above- 0°F CCA	750
--- 0°C(32°F) to 10°C(50°F)- 0°F CCA	750
---18°C(0°F) to 0°C(32°F)- 0°F CCA	750
Max. allowable resistance of Starting circuit	0.002ohm
Starter(heave,Anode)	DC24V
Battery recharge system, negative ground	70ampere

Alternator specification


Phases	3
Poles	4
Power factor(cosφ)	0.8
Winding connection	Star
Winding pitch	2/3
Voltage regulator type	AVR

Coating	Vacuum impregnation
Insulation class	H
Protection	IP23
Excitation system	Self-excited
Bearing	Single Bearing
Coupling	Flexible disc

Control system Introduction

Deepsea 6120 Auto start & auto mains failure control panel

Deepsea 6120 is an auto mains failure controller for single generator, it can monitor and protect the generator working all the time. it has a LCD display which clearly shows the status of the engine. this controller include seven inputs and six outputs. This controller can also be programmed using the front panel or by using DSE configuration Suite PC software



Key Features:

- Auto start/stop, load transfer and alarming of generator
- Remote start on or off load
- With hierarchical loading function
- Multiple start/stop cycles can be preset
- 3 phase generator and mains voltage monitoring.
- Generator/load power detection(kW, kVA, kVA_r PF)
- Overload protection (kW)
- Load current monitoring and protection
- Engine speed protection
- Engine pre-heat
- Engine start idle & stop idle
- Battery voltage monitoring
- Start under the low battery
- 4 active outputs
- 4 digital inputs and 3 analogue inputs.
- 6 Custom digital input
- 6 outputs(4 configurable on magnetic pick-up, 6 configurable on Canbus version)
- DSE2130,DSE2157,DSE2548 expansion module can be connected
- Support 0-10V or 4-20mA oil pressure sensor

Main features:

- Multi language display
- Mains failure self starting
- The running time of the engine can be recorded to facilitate the maintenance and repair of the unit
- User-friendly set-up and button layout
- LCD display can display multiple parameters at the same time
- Support EFI engine
- IP65 rating (with optional gasket)
- PC and front panel configuration
- 100 event records
- Data recording and trend analysis

Protection:

- Two sets of protection parameters can be preset
- Normal alarm, electrical trip and shutdown alarm can be set to effectively monitor the engine speed,oil pressure, water temperature and oil level, as well as the frequency, voltage, current and power of the alternator, for complete engine/alternator protection
- Low Oil Pressure
- High water Temperature
- High voltage and low voltage
- Overspeed
- Emergency stop
- Fail to start

Soundproof Canopy Introduction:

Standard Type :

- The arc angle structure makes the appearance beautiful and not easy to bump
- High quality coating powder, chemical surface treatment & 100-120um coating thickness greatly improving the anti-corrosion and anti rust level
- Stainless steel hinge & door lock are beautiful and anti-rust
- 2.0mm cold rolled plate used makes the body more solid
- The bottom forklift and loading port design enables easy loading and unloading
- The drainage outlets are all connected to the outside for easy operation
- The sufficient air in & out design ensure long-term and stable operation of the unit
- Isolation net is designed for air inlet, exhaust outlet and muffler outlet to prevent objects from entering the unit
- High density foam used inside effectively reduces noise
- Ceiling Lighting is equipped for easy operation
- The built-in base fuel tank with fuel filler set on the shell facilitates refueling
- Models above medium power range are designed with top hoisting mechanism to facilitate transportation of the unit.

Imitated container type :

- The shell is made of 3.0mm hot rolled steel plate so as to withstand the lifting capacity of 15-ton without deformation
- The switch cabinet and control panel are respectively set on both sides of the shell for easy maintenance & operation
- The shell looks similar to standard container, and can be loaded into 40HQ container for transportation, which is convenient for shipping
- The lifting eye holes are designed on the top same as the standard container for easy handling
- High density foam used inside effectively reduces noise
- The built-in base fuel tank with fuel filler set on the shell facilitates refueling
- Double emergency stop button set on different surfaces enables quick response to operation requirements
- The shell base is independent from the unit with 3mm thick checkered steel plate floor, which is beautiful & antiskid, and is convenient for overhaul & maintenance of the unit
- The door handle, lock and hinge are all made of stainless steel to avoid rusting
- The air out louver made of the mesh plate with powder coating and pasted with high-density glass fiber is beautiful and not easy to rust, and can further reduce the noise
- Isolation net is designed for air inlet, exhaust outlet and muffler outlet to prevent objects from entering the unit
- The sufficient air in & out design ensure long-term and stable operation of the unit
- The drainage outlets are all connected to the outside for easy operation
- Ceiling Lighting is equipped for easy operation

Classics Economic series :


- Right angle around the canopy
- Carbon spray hinges and lock with rust proof
- The drainage & lubricating oil outlets are all connected to the outside for easy to maintain
- The air inlet and outlet are designed with grid structure of to prevent big objects from entering the canopy
- The lifting lug on the top for medium range genset makes easily and convenient transportation
- High-quality powder coated, chemical surface treatment & 80-120um coating thickness is highly durable against erosion and scratch
- The bottom forklift is built-in base frame for small range genset, with over stow capacity
- The fuel inlet on the canopy is for easy to fuel filling
- High-density sponge to effectively reduce noise



Classics Economic Canopy Sample Picture



Standard supply scope:



Optional supply scope:

Genset	Engine	Alternator	Control system
<ul style="list-style-type: none">• Tool box• Base fuel tank• External daily fuel tank• Trailer	<ul style="list-style-type: none">• Fuel heater• Fuel and water separator	<ul style="list-style-type: none">• Temp. detector for winding and bearing• PMG• Antirust, mildew and salt fog treatment• Anti condensation heater	<ul style="list-style-type: none">• ATS• Synchronization System• Adjustable earth relay
Breaker	Fuel system	Lub-oil system	Cooling system
<ul style="list-style-type: none">• ABB• Schneider	<ul style="list-style-type: none">• Low fuel level alarm• Auto Fuel Pump• T Vlave	<ul style="list-style-type: none">• Lub oil heater• Temp.-sensor• Oil drain Pump	<ul style="list-style-type: none">• Elec.coolant Heater



SPARTAN

Spartan UK | Spartan China | Spartan UAE
info@spartanenergy.co.uk | www.spartanenergy.co.uk

-  Follow us @facebook.com/spartanenergy
-  Follow us @linkedin.com/spartanenergy
-  Follow us @spartanenergy

All information in the document is substantially correct at the time of printing but maybe subsequently altered by the company.

Distributed by



ENGINEERING SUPPLIES LTD.